TECHNICAL DATASHEET

- Upper made of breathable, threedimensional fabric, reinforced with split leather
- Very light and flexible
- Maximum comfort
- High level of SRC anti-slip properties
- Comfortable insole made of EVA foam
- Reflective elements for better visibility



## **DESCRIPTION**

Safety shoes made of one piece of highly breathable, three-dimensional fabric reinforced with split leather. There are no metal elements in this model - a fiberglass toe cap and a textile anti-puncture insert. The sole is made of dual-density polyurethane, pulled up in the toe and heel areas to additionally protect these areas in forced positions such as kneeling.

## **PARAMETERS**



| UPPER                                     |            | Breathable, three-dimensional fabric with a diamond structure.  Toe cap, heel and laces areas reinforced with a split leather. |  |                   |                     |  |
|---|------------|--|--|-------------------|---------------------|--|
| LINING -                                  | BACK       | Absorbent and breathable 3D fabric, heel area reinforced with a technical fabric   |  |                   |                     |  |
| LIMINO                                    | FRONT      | Unwoven fabric made of agglomerated fibres in gray colour  |  |                   |                     |  |
|   | TONGUE     | The outer part is made of a black, abrasion resistant Cordura and split leather, the inside is made of breathable 3D fabric.   |  |                   |                     |  |
|   | INSIDE     | High strength and zero penetration fabric.   |  |                   |                     |  |
|   |            | COMPOSITION  | PU/PU  |                   |                     |  |
|   |            |  | CD A   | plane             | 0,38                |  |
|   |            | SLIP FACTOR  | SRA  | heel              | 0,34                |  |
| OUTSOLE                                   |            | SLIP FACTOR  | SRB  | plane             | 0,19                |  |
|   |            |  |  | heel              | 0,16                |  |
|   |            | QUALIFICATION  | SRC  |                   | 1000                |  |
| TOE CAP Non-magnetic, anatomical, in 200J |            |  | tomical, insu                                    | ılating, stainles | ss fiberglass 45g > |  |
| ANTI-PUNCTU                               | JRE INSOLE | Multilayer fabric made of interwoven anti-puncture fibers (1100N)  |  |                   |                     |  |
|   | INSOLE     | Comfortable insole of EVA foam   |  |                   |                     |  |
|   |            | SIZES  | 36-49  | 36-49             |                     |  |
| OTHER PARAMETERS                          |            | WEIGHT   | 987g   | 987g              |                     |  |
| OTHER PA                                  | RAMETERS   | OTHER  | Reflective elements on the sides and at the back |                   |                     |  |



1











NON-METALLIC TOE

NON-METALLIC ANTI- ANTISTATIC PROPERTIES SHOCK-ABSORPTION OUTSOLE RESISTANT TO COLD INSULATION PUNCTURE INSOLE IN THE HEEL AREA OILS

SLIP RESISTANCE